

DISINFECTION SYSTEMS

BSV.
with you since 1984



“BSV” Pro 250 - 1000 Series Commercial Salt Chlorinators Made In Spain

**MODULAR SALT WATER CHLORINATOR.
PRODUCTIONS FROM 250 TO 1000 GRAMS /
HOUR. USEFUL ON COMMERCIAL AND
PROFESSIONAL POOLS.**

- ✓ Lower electrical consumption
- ✓ (IP21) Index protection
- ✓ Lower operating temperature
- ✓ Better output of the salt water chlorination by using a last generation switch mode power supply
- ✓ Longer durability of the electrolysis cell
- ✓ Internal microprocessor control, that determines the device operating hours
- ✓ Digital display, easy and intuitive use control

- When the water in the pool exceeds a temperature of 28°C regularly, select the production immediately higher than indicated by the table.
- The number of bathers per day is very important value in Semi-Public Swimming pools. If this parameter is bigger than above, the Salt Chlorinator system needs to be calculated again.



LC Long Life Cell
 12K 12.000 Hours
 Low weight
 AUTO Automatic
 MPT
 Low Consumption

grams / hour =	$2 \text{ ppm} \times \text{Volume of Pool (m}^3) + (14 \times \text{Bading load per day})$ Filtration Turnover / day (hour)
กรัม / ชั่วโมง =	$2 \text{ ppm} \times \text{ปริมาณน้ำในสระ (m}^3) + (14 \times \text{จำนวนคนลงสระต่อวัน})$ จำนวนชั่วโมงของระบบกรองต่อวัน

Start up salt quantity is 5kgs per 1 m³ volume of water

Code	Model	Gram/Hour	In & Outlet (Inches)
20900210080	Pro-250-V2 *	250	3
20900210085	Pro-500 *	500	3
20900210090	Pro-750 *	750	3
20900210095	Pro-1000 *	1000	3

* สินค้าไม่มีสต็อก กรุณาสั่งล่วงหน้า 30-60 วัน / No Stock, Delivery Time 30-60 Days