

# FILTERS



## “EMAUX” CF Series Cartridge Filters

### FEATURES

- Compact and lightweight
- UV resistant tank
- Heavy duty ring-lock lid allows easy cleaning and replacement of the cartridge element
- Screw type air bleeder for easy removal of trapped air inside the filter tank
- High-quality oil-filled pressure gauge for easy inspection of the operation pressure
- Application to domestic swimming pool & spa
- Maximum Working Pressure 250kPa /36psi /2.5bar
- Maximum Water Temperature 40°C (100°F)




### CF SERIES FILTER IS EQUIPPED WITH

1. Universal standard of union connection
2. Pressure gauge
3. Cartridge filter element

### Product Information:

Model	Filter Area (m <sup>2</sup> )	Valve Connections	Max Flow Rate	A mm	B mm	C mm
CF25	2.25	1.5" / 50mm	92lpm 5.5m <sup>3</sup> /h	445	387	225
CF50	4.63	1.5" / 50mm	190lpm 11.4m <sup>3</sup> /h	625	567	225
CF75	7.00	1.5" / 50mm	283lpm 17.0m <sup>3</sup> /h	805	747	225
CF100	9.40	2.0" / 63mm	382lpm 22.9m <sup>3</sup> /h	985	927	225
CF150	13.72	2.0" / 63mm	555lpm 33.4m <sup>3</sup> /h	1165	1107	225
CF200	16.82	2.0" / 63mm	680lpm 40.9m <sup>3</sup> /h	1345	1287	225



#### Tank Material

UV Resistant Plastic

#### Max Operating Pressure

36 psi / 2.5 bar

#### Max Temperature

40°C (104°F)

Code	Model	In/Outlet (inches)	Sq.Ft.	Flowrate (gpm)	Flowrate (m <sup>3</sup> /h)	Height (cm)	Width (cm)
20510510005	CF25	1.5	25	25	5.5	44.50	22.50
20510510010	CF50		50	50	11.4	62.50	
20510510015	CF75		75	75	17.0	80.50	
20510510020	CF100	100	100	22.9	98.50		
20510510025	CF150	2	150	147	33.4	116.50	
20510510030	CF200		200	180	40.9	134.50	