



## “GREENCO” Commercial Air Blowers Complete Set With Unions

### FEATURES

- All 2RB achieve the standards and norms of the low voltage directive (LVD) 2006/95/EC, rotating electro technical motor EN 60034-1-2004, electromagnetic compatibility (EMC) EN55014-1/2, EN61000-2/-3/-4/-6
- For standard UL for ELECTRIC MOTOR UL 1004-1
- Relief-valve are available for limiting differential pressure
- Measuring-surface sound-pressure level ac. To DIN EN 21680, measured at a distance of 1 m. the pump is throttled to an average suction pressure, a hose is connected to the discharge side (compressor) / suction side (vacuum pump), but is not fitted with relief valves.
- The motor are designed according to the DIN EN 60 034 / DIN IEC 34-1 and temperature class F



Code	Model	In/Outlet (inches)	Max Flowrate (m <sup>3</sup> /hr)	Sound Pressure Level (dB)	Amp	In/Outlet (inches)	H.P.	Voltage	Phase
20800700005	2RB 410-7AA11	1.5	145	63	3.39	1.5	1.0	220	1
20800700010	2RB 510-7AA11	2	210	64	5.0	2	1.5	220	1
20800700015	2RB 510-7AA21	2	210	64	6.8	2	2.0	220	1
20800700020	2RB 610-7AH16	2	220	69	5.7	2	3.0	380	3
20800700025	2RB 710-7AH26	2	318	69	7.8	2	4.0	380	3
20800700030	2RB710-7AH37	2	318	69	9.7	2	5.0	380	3
20800700035	2RB 810-7AH17*	2.5	530	70	14.4	2.5	7.5	380	3
20800700040	2RB 810-7AH27*	2.5	530	70	19.7	2.5	10.0	380	3

\* สินค้าไม่มีสต็อก กรุณาสั่งล่วงหน้า 60-90 วัน / No Stock, Delivery Time 60-90 Days