

PUMPS MAX E-PRO



Featured Highlights

- **Typical Installation** – Inground pools, pool/spa combinations, inground spas, fountains and water features
- **Self-priming** – Suction lift up to 15 ft. above water level
- **Easy-to-Install** – 2 in. ports include external and internal threads for more plumbing options
- **Superior Hydraulic Design** – Moves larger volumes of water, resulting in lower operating costs
- **Impeller Manufactured with PPO Resin** – Withstands the toughest water environments
- **EDPM Rubber Shaft Seal** – Longer-lasting seal stands up to the harshest environments
- **Self-lubricating Lid O-ring** – Does not require lubricant

P6 & 5P6R SERIES – High efficiency, low maintenance and maximum performance—all the features demanded by today’s pool professionals. The Max-E-Pro pump has our new Quick-Lock™ Trap Cover Ring and the 2 in. ports incorporate internal and external threads. Available in single- and two-speed models, with ratings from 1/2 to 3 HP. **Built with quality construction** using a durable one-piece pump housing constructed of Dura-Glas™—Sta-Rite’s industry leading glass-reinforced composite resin. **Fast cleaning** with a new Quick-Lock trap cover ring permits fast access to strainer basket. Large see-through lid makes it simple to check for debris. A **strong, sturdy**, specially-designed base dampens sound and vibration, making the Max-E-Pro pump one of the quietest pumps in its class.

A- VARYING LENGTH

HP	STD EFF	EE	3PHTEFC
.5	26.92		
.75	26.92		
1	27.29	28.45	24.76
1.5	28.92	28.45	24.76
2	28.92	29.08	25.17
3.0	28.92	29.08	25.87

Dimensions and Performance

